

TECHNICAL DATASHEET

CIBUM COMPTEC 140 ISO 46



Nonfood Compounds
Program Listed H1
Reg. No.: 165837

PRODUCT DESCRIPTION

CIBUM COMPTEC 140 ISO 46 is a synthetic compressor oil based on base stock 4 and 5.

CIBUM COMPTEC 140 ISO 46 is specially designed for lubrication of screw, piston and vane compressors requiring a ISO 46 viscosity. The synthetic base fluids in combination with a special additive package provides extended lubrication life and a unique protection against wear, rust, and corrosion.

Test has proven that CIBUM COMPTEC 140 ISO 46 ensures + 5.000 operating hours*

When switching a used compressor oil to a different technology or different brand, we highly recommend consulting with your local CIBUM agent.

CIBUM COMPTEC 140 ISO 46 is registered under No.165837 at NSF according to H1 regulations for lubricants with incidental food contact.

CIBUM COMPTEC 140 ISO 46 is manufactured in an ISO 21469 certified facility.

* Subject to proper operating conditions


TECHNICAL DATA

Base Oil	Synthetic blend	
Colour	Visual	Yellowish
Density	ISO 12185	835 Kg/m ³
ISO Grade	ASTM	46
Viscosity Index	ISO 2909	> 120
Base Oil Viscosity at 40°C	ISO 3104	47,2 cSt
Base Oil Viscosity at 100°C	ISO 3104	9,3 cSt
Flash Point	ISO 2592	> 250° C
Pour Point	ISO 3016	-40° C
Copper Corrosion (3h/100°C)	ISO 2160	1a (3h/100°C)
RPVOT	ASTM D2272	> 1000 min
Recommended Temperature Range	-30°C to + 120°C	

Extended Oil Life Time

Food-Grade Compressor Oil

Unique High-Temperature Stabilities



Shelf life: 3 years from date of manufacture, Batch coding durability are printed on label to each unit.

Storage: Store unopened in 5° - 20°C, must be stored dry and away from products with odors.

Cibum Lubricants
Erritsoe Mollebanke 10
7000 Fredericia
Denmark

Phone + 45 36981899
Web: cibum-lubricants.com
Mail: mail@cibum-lubricants.com