



CIBUM PURA-TORQUE FG-HD



PRODUCT DESCRIPTION

CIBUM PURA-TORQUE FG-HD is a semi-synthetic based lubricant with synthetic polymer system to provide superior wear and corrosion protection in food- and beverage- industry machinery applications. CIBUM PURA-TORQUE FG-HD is the ideal multi-purpose lubricant for food processing applications, with the highest performance on chains and high-loaded chains in sterilizers and pasteurizers. The exceptional formulation ensures a strong lubricating film with minimal drip for perfect protection of rollers, cams, slides, and chains at most speeds.

CIBUM PURA-TORQUE FG-HD is compatible with most mineral oils, synthetic oils, and seals (is not compatible with polyglycol based lubricants).

CIBUM PURA-TORQUE FG-HD is registered under No. 167701 at NSF according to H1 regulations for lubricants with incidental food contact.


CIBUM PURA-TORQUE FG-HD do not contain genetically modified ingredients (GMO), or hydrogenated fats. CIBUM PURA-TORQUE FG-HD is suitable for Kosher applications and for Halal applications. CIBUM PURA-TORQUE FG-HD is acceptable for incidental Food Contact (H1) and meets the requirements FDA § 27 of Article 21 CFR 178.3570. CIBUM PURA-TORQUE FG-HD meet the European Parliament and Council Regulation (EC) No 1935/2004 of 27 October 2005, as Decree No 502 of 19 August 2005.

TECHNICAL DATA		
Base Fluid	Semi-Synthetic	
Propellant	Propan, Butan and Isobutan	
Color	Visual	Milky-White
Base Oil Viscosity at 40° C	ASTM D7152	180 cSt
Base Oil Viscosity at 100° C	ASTM D7152	19.2 cSt
Base Oil Pour Point	ISO 3016	-22° C
Base Oil Flash Point	ISO 2592	256° C
Propellant Flash Point	ISO 2592	- 60° C
Spray Pattern	Jet Stream	
Rust Test Method A (Distilled Water)	ASTM D665	Pass
Rust Test Method B (Synthetic Sea Water)	ASTM D665	Pass
Recommended Temperature Range	-25° C to + 90° C	

Good resistance to shock loads

High Performance Chain Lubricant

Superior Wear- And Corrosion Protection



Shelf life: 5 years from date of manufacture, Batch coding durability are printed on label to each unit.

Storage: Store unopened in 0° - 40° C, must be stored dry and away from heating sources max 50° C.

Cibum Lubricants
 Erritsoe Mollebanke 10
 7000 Fredericia
 Denmark

Phone + 45 36981899

Web: cibum-lubricants.com

Mail: mail@cibum-lubricants.com