

CIBUM PURA-TORQUE FG



PRODUCT DESCRIPTION

CIBUM PURA-TORQUE FG is a semi-synthetic based lubricant with synthetic polymer system to provide superior wear and corrosion protection in food- and beverage- industry machinery applications. CIBUM PURA-TORQUE FG is the ideal multi-purpose lubricant for food processing applications, with the highest performance on chains, overhead-chains, in gear-boxes and high-speed oil lubricated seamers. The exceptional formulation ensures a strong lubricating film with minimal drip for perfect protection of rollers, cams, slides and chains at most speeds.

CIBUM PURA-TORQUE FG is compatible with most mineral oils, synthetic oils and seals (is not compatible with polyglycol based lubricants).

CIBUM PURA-TORQUE FG is registered under No. XXXXXX at NSF according to H1 regulations for lubricants with incidental food contact.

CIBUM PURA-TORQUE FG do not contain genetically modified ingredients (GMO), or hydrogenated fats. CIBUM PURA-TORQUE FG is suitable for Kosher applications and for Halal applications. CIBUM PURA-TORQUE FG is acceptable for incidental Food Contact (H1) and meets the requirements FDA § 27 of Article 21 CFR 178.3570. CIBUM PURA-TORQUE FG meet the European Parliament and Council Regulation (EC) No 1935/2004 of 27 October 2005, as Decree No 502 of 19 August 2005.



TECHNICAL DATA

Base Fluid	Semi-Synthetic	
Color	Visual	Transparent
Base Oil Viscosity at 40° C	ASTM D7152	151.0 cSt
Base Oil Viscosity at 100° C	ASTM D7152	15.8 cSt
Viscosity Index	ASTM D2270	>105
Viscosity Grade	150	
Pour Point	ISO 3016	-22°C
Flash Point	ISO 2592	245°C
Fire Point	ASTM D92	285°C
4-Ball Wear, Scar Diameter	ASTM D4172	0.37 mm
Rust Test Method A (Distilled Water)	ASTM D665	Pass
Rust Test Method B (Synthetic Sea Water)	ASTM D665	Pass
Recommended Temperature Range	-10°C to + 100°C	

Ideal Multi-Purpose Lubricant

High Performance Chain Lubricant

Superior Wear- And Corrosion Protection



Shelf life: 3 years from date of manufacture, Batch coding durability are printed on label to each unit.

Storage: Store unopened in 0° - 40°C, must be stored dry and away from products with odors.

Cibum Lubricants
Erritsoe Mollebanke 10
7000 Fredericia
Denmark

Phone + 45 36981899
Web: ciblub.com
Mail: mail@ciblub.com