

CIBUM ICTUS AQUA



PRODUCT DESCRIPTION

CIBUM ICTUS AQUA is a silicate thickened lubricating grease especially developed for expansion valves, water pumps and water taps.

CIBUM ICTUS AQUA is suitable for both food industries and tap water-equipment industry.

CIBUM ICTUS AQUA is EPDM compatible H1 grease and recommended for seals, low-loaded bearings, valves and water pumps needing a silicone grease.

CIBUM ICTUS AQUA is certified according to positive list (contact with water intended for human consumption) under N° 15 CLP LY 011, USDA/FDA H1, CLP and ACS.

CIBUM ICTUS AQUA is certified HALAL and KOSHER.

TECHNICAL DATA

Base Oil	Silicone Oil	
Thickener	Silicate Gel/PTFE	
Color	Visual	Colourless/Opaque
Texture	Smooth	
Base Oil Viscosity at 25° C	ASTM D7152	1000 cSt
Base Oil Viscosity at 40° C	ASTM D7152	700 cSt
Base Oil Viscosity at 100° C	ASTM D7152	226 cSt
Penetration 60 Strokes	ISO 2137	220-250
Water Resistance at 90° C	DIN51807:1	1-90
Recommended Temperature Range	-52° C to +155° C	

CIBUM ICTUS AQUA is acceptable for incidental Food Contact (H1) and meets the requirements FDA § 27 of Article 21 CFR 178.3570. CIBUM ICTUS AQUA meets the European Parliament and Council Regulation (EC) No 1935/2004 of 27 October 2005, as Decree No 502 of 19 August 2005. CIBUM ICTUS AQUA is certified according to positive list (contact with water intended for human consumption) under N° 15 CLP LY 011, USDA/FDA H1, CLP and ACS.

Compatibility With EPDM

Safe For Use In Water Taps

Certified According to H1/CLP/ACS



Shelf life: 3 years from date of manufacture, Batch coding durability are printed on label to each unit.

Storage: Store unopened in 5° - 20° C, must be stored dry and away from products with odors.

Cibum Lubricants
 Erritsoe Mollebanke 10
 7000 Fredericia
 Denmark

Phone + 45 36981899
 Web: cibum-lubricants.com
 Mail: mail@cibum-lubricants.com